



knürr
World of control rooms

CONTROL ROOM SOLUTIONS BOOK

2026 / EN-V4

WORKPLACE LIGHTING

261 to 270



Levels Of Workplace Lighting

From an ergonomic point of view a workplace structures in several access areas. Knürr divides these in three different areas:

- **Task**
 - Area of immediate manual activity. Space for mouse, keyboard, writing utensils and communication devices. Task lights are meant to selectively illuminate the area directly in front of the operator. This light shall not affect other workstations and can be dimmed and adjusted.
- **Room Level**
 - Ceiling-mounted lamps are of advantage for an unobstructed view to a monitor wall. These overhead lamps illuminate the console with direct and indirect light and subsequently can be integrated in the room illumination. GST18 connector system, DALI and radio control allow for an easy installation.
- **Workstation**
 - Area of immediate manual activity and furthermore the complete remaining work surface of the console. Installed with overhead extension arms or as underfit lamp. Light sources allow 500



Task

DAA20082



Workstation

DAA20055



Room Level

ACC20013

Task


Knürr® Task LED

The Knürr Task LED is fitted with a bright LED lamp that provides pleasant task lighting and an easily accessible dimming button.

A specially developed highly reflective plastic reflector ensures glare-free working. What's more, even with such impressive performance figures, the Knürr Task LED is surprisingly economical in terms of energy consumption, with only 8 W of installed consumption for an average illuminance of up to 700 lx.

- Light and easy to adjust to your individual position
 - Specially developed reflector for glare-free lighting
 - Switching and dimming with memory function via easily accessible control button in the luminaire head
 - Automatic cut-off and switch-on behavior can be adjusted
 - Maintenance free LED technology with a service life of up to 50,000 hours and more
- **Technical data**
 - Color temperature neutral white 4,000 K
 - Connected load 100-240 V; 50/60 Hz
 - Power consumption approx. 8 W
 - Luminous flux approx. 600 lm
 - Luminous efficacy approx. 75 lm/W
 - Illuminance efficiency factor 93 lx/W
 - Color rendering index (CRI) >80 (typ.85)
 - Supplied with 3 m mains lead and with mains plug type CEE 7 / 16 (Euro plug),
 - Various fastenings as accessories
 - **Color**
 - Aluminum black coated (for Task LED and Task LED L version)
 - Silver metallic for Task LED SL
 - **Supply schedule**
 - 1 Knürr Task LED
(Please always order mounting adapter of choice)

Description	Model		Order no.	UP
Knürr® Task LED L	3 hinges (2 arms) Color: black	long/short	00.350.174.9	1 unit
Knürr® Task LED SL	3 hinges (2 arms) Color: silver metallic	short/long	00.350.174.7	1 unit



Knürr Task LED

DAA20082



Knürr Task LED L

DAA20083



Knürr Task LED SL

Task

Screen Bar Halo

- **Technical data**
 - Light colour: 2,700 Kelvin warm white / 6,500 Kelvin daylight white
 - Dimmable: Yes
 - Colour: Grey
 - Base: Clamp base
 - Colour rendering index (CRI) Ra=95
 - Luminance:
 - Central illuminance 800lux (height 45cm)
 - Illuminance (at 500 lux) 63cm x 40cm
 - Power supply
 - Power input 5V / max.1.3A USB port
 - Power consumption 6.5 Watt (Max.)
- **Supply schedule**
 - 1 light
 - **Note**
 - The light is usually powered directly via the monitor's USB port.
 - If a separate power supply unit is required, this must be ordered separately.




Description	Order no.	VE
Screen Bar Halo	00.350.213.9	1 unit

Task

Nano-LED

The Knürr Nano LED ensures uniform and glare-free illumination, which reduces eye fatigue. This contributes to an ergonomic and pleasant working environment. Precise illumination of the work surface supports concentration and promotes efficiency when carrying out tasks.

- **Technical data**
 - Protection class: IP20 Area of application: Indoors
 - Luminous intensity: 511 lm
 - Light color: 4000 K Color rendering: CRI = 97 Service life: L85 / 50000 h
 - Color consistency: initial MacAdam = 3 SDCM
- **Supply schedule**
 - 1 Knürr Nano LED B400 with attachment to TFT holder
 - 1 push-button unit, 1 power supply unit



Nano-LED

• LED •

Description	Model	Order no.	UP
Nano-LED	Nano LED 1 monitor	00.350.206.9	1 unit
Nano-LED	Nano LED 2 monitors	00.350.206.9.000001	1 unit
Nano-LED	Nano LED 3 monitors	00.350.206.9.000002	1 unit
Nano-LED	Nano LED 4 monitors	00.350.206.9.000003	1 unit
Nano-LED	Nano LED 5 monitors	00.350.206.9.000004	1 unit



Dimensions in mm: W = Width
 H = Height
 D = Depth
 h = Installation height
 d = Useful depth
 L = Length

HU = Standard height unit, 1 HU = 44.45 mm
 19" = 482.6 mm,
 (ideal for 19" components in acc. with DIN 41494)

UP = Unit of packaging
 kg = Weight

Conversion: 1 inch = 25.4 mm
 1 pound = 453.6 g

Replace „x“ with the number of your color choice

Task

Mounting Adaptors

• Important information

- Our workstation lamps are supplied as standard with a universal adapter. Please order the corresponding adapter or the respective Knürr Console.

Universal mounting adaptor

- for fixation at tabletops with a max. height of 70mm

• Supply schedule

- 1 Adaptor
- Mounting material

• Color/Surfaces

- Plastic / Aluminum powder coated

• Versions

Functional rail

- for Installation on functional rails as used with Ergocon, Elicon or Dacobas

Dacobas Profile

- for T-Slot installation on Dacobas and Elicon profiles at any height

Tabletop

- for direct installation in the tabletop

Dacobas/Elicon Profile (top)

- for fixation at the top side of Dacobas or Elicon Profiles

System	Color	Order no.	UP
Functional rail	RAL9006 white aluminium	01.316.225.9	1 set
Dacobas Profile	RAL9006 white aluminum	01.316.256.9	1 set
Tabletop adaptor	Black	00.350.181.9	1 unit
Dacobas-Profile (top)	RAL5008 grey blue	00.350.156.1	1 set
Elicon-Profile (top)		00.351.031.7	1 set
Universal mounting adaptor	Black	00.350.180.9	1 unit



DAA20053

Mounting adaptor for functional rail



ACC20014

Mounting adaptor for Dacobas-Profile (side)



DAA20085

Tabletop mounting adaptor



DAA20086

Tabletop mounting adaptor



DAC20036

Mounting adaptor for Dacobas-Profile (top)



CON20017

Mounting adaptor for Elicon-Profile (top)



ACC20050

Universal mounting adaptor

Workstation

Technical substructure lighting with magnetic fastening

- Economical and space-saving solution for lighting cabinets and enclosures. State-of-the-art LED technology guarantees a long and maintenance-free service life
- The most important features are:
 - Integrated motion sensor or switch
 - easy magnetic mounting for more flexibility
 - Combined AC & DC voltage range allows universal use with a single model
 - Wieland connector for quick and easy installation
- Material / Surface**
 - PC plastic
- Dimensions**
 - Width: 400 mm
- Supply schedule**
 - 1 luminaire
- Note**
 - Please order desired cable separately



Technical substructure lighting

Type	Order no.	UP
Light with motion sensor (PIR)	00.350.158.1	1 unit
Light with switch	00.350.158.2	1 unit
Connecting cable LED light 2 metres	00.350.158.3	1 unit

Dimensions in mm: W = Width
H = Height
D = Depth
h = Installation height
d = Useful depth
L = Length

HU = Standard height unit, 1 HU = 44,45 mm
19"= 482,6 mm,
(ideal for 19" components in acc. with DIN 41494)
UP = Unit of packaging
kg = Weight

Conversion: 1 inch = 25,4 mm
1 pound = 453,6 g

Replace „x“ with the number of your color choice

Workstation

Knürr Lumax LED Lamp Workstation or system installation

- State of the art LED-Modules for highest efficiency
- Glare free
- Photometric properties checked according to DIN EN 13032-1
- Overdimensioned LED-Modules allow for dimming in the first years of use and thus grant extremely longevity
- Dimmable with „Touch DIM“ feature via push button on the lamp or at tabletop
- Perfect fit for Knürr's consoles (adaptors for Knürr's multi functional rails)
- 20° tiltable

Material

- Sheet steel powder coated

Color combinations

Lamp:

- Metallic grey microstructure

Side cover:

- RAL 9007 grey aluminum microstructure

Version system lamp:

- .9 = supports in metallic grey microstructure
- .7 = supports in RAL 9006 white aluminum

Technical Data (W1140)

Dimensions:

- Width: 1140 mm
- Height: 30 mm (without mounting adapter)
- Depth: 100 mm

Light:

- Luminous flux 2160 lm
- Luminous efficiency: 80 lm/W
- Color temperature: 4000 K
- Color rendering index: Ra > 80
- SDCM: 4
- Dimming range: 1 – 100%
- Average lifetime (LED): 50.000 h

Electrical:

- Power consumption max. 27 W
- Power supply: 220 – 240 V 50/60 Hz

Technical Data (W1700)

Dimensions:

- Width: 1700 mm
- Height: 30 mm (without mounting adapter)
- Depth: 100 mm

Light:

- Luminous flux 3255 lm
- Luminous efficiency: 83 lm/W
- Color temperature: 4000 K
- Color rendering index: Ra > 80
- SDCM: 4
- Dimming range: 1 – 100%
- Average lifetime (LED): 50.000 h

Electrical:

- Power consumption max. 39 W
- Power supply: 220 – 240 V 50/60 Hz

Supply schedule

- 1x LED lamp with integrated LED driver
- Version with offset switch:
1x module with external push button for switching and dimming
- Overhead system lamp:
with adaptors to Knürr's multi functional rail
- 1x Schuko lead (3m)
- Mounting material

How supplied

- Pre-assembled



ACC20016

• LED •




Knürr Lumax LED Lamp

DAA20055



Workstation lamp (underfit)



System lamp

Description	Model	Order no.	UP
Knürr Lumax LED 1140U 4000K int.	Workstation lamp with integrated push button	00.350.182.9	1 unit
Knürr Lumax LED 1140U 4000K ext.	Workstation lamp with offset push button (below table top)	00.350.183.9	1 unit
Knürr Lumax LED 1700U 4000K int.	Workstation lamp with integrated push button	00.350.186.9	1 unit
Knürr Lumax LED 1700U 4000K ext.	Workstation lamp with offset push button (below table top)	00.350.187.9	1 unit
Knürr Lumax LED 1140B 4000K ext.	System lamp with offset push button (below table top)	00.350.185.7	1 unit
Knürr Lumax LED 1140B 4000K ext.	System lamp with offset push button (below table top)	00.350.185.9	1 unit
Knürr Lumax LED 1700B 4000K ext.	System lamp with offset push button (below table top)	00.350.189.7	1 unit
Knürr Lumax LED 1700B 4000K ext.	System lamp with offset push button (below table top)	00.350.189.9	1 unit
Fixation kit for worktop installation	for system lamp	00.350.198.7	1 unit

Workstation

Knürr Smart LED

Modern LED underfit lamp for installation beneath a workstation superstructure level.

- LED technology for optimum energy efficiency
 - Frosted glass cover prevents direct glare
 - Integrated electronic power supply for a slim design
 - Easy to reach on/off switch
 - lamp tiltable by 15°
 - Simple assembly
- **Material**
 - Sheet-steel, powder-coated
 - **Finish**
 - Powder-coating RAL 9006 white-aluminum
- **Technical Data**
 - Dimensions:**
 - Overall height: approx. 80 mm
 - Overall width: see table
 - Light:**
 - Luminous flux:
 - 1100 lm (version W 700 mm)
 - 1780 lm (version W 1300 mm)
 - Color of light: neutral white (EN 12464-1)
 - Color temperature: 4000 K
 - Color rendering index: Ra > 80
 - Electrical:**
 - Power consumption max.
 - 10 W (version W 700 mm)
 - 18 W (version W 1300 mm)
 - Power supply: 220 – 240 V 50/60 Hz
 - Integrated on/off switch
 - C13 mounting socket
 - 2.0m Schuko power cord
 - **Supply Schedule**
 - 1 Lamp Smart LED
 - 1 Mounting material
 - 1 Power cord

Model	W	Order no.	UP
Underfit lamp	700	00.350.190.9	1 unit
Underfit lamp	1300	00.350.191.9	1 unit

• LED •



ACC20017

• LED •



Knürr Smart LED

ACC20018

Dimensions in mm:	W = Width	HU = Standard height
	H = Height	unit, 1 HU = 44.45 mm
D = Depth	h = Installation height	19" = 482.6 mm,
	d = Useful depth	(ideal for 19" components
L = Length		in acc. with DIN 41494)
		UP = Unit of packaging
Conversion:	1 inch = 25.4 mm	kg = Weight
	1 pound = 453.6 g	Replace „x“ with the number of your color choice

Workstation

Knürr® LED pendant

Pendant luminaire. Suspended ceiling mount in extra flat design does not block the view to large screen display walls with multiple console desks. Direct light portion with Edgelight and Lightguide technology for homogeneous light emission. Indirect light portion with Batwing diffusor for a wide light emission. Absolutely glare-free. Variable ceiling distance allows use in room heights from 2.5 and 4.2 m. Easy installation: Only needed is a Schuko or GST18 socket in the ceiling. Control is radio-controlled via BT module.

- **Finish**
 - Powder-coated white
- **Material**
 - Sheet-steel, powder-coated
 - Lamp cover: Acrylic (PMMA) clear (colorless)

- **Technical Data**
 - Fitted with LED
 - Connection: 220 – 240 V; 50/60 Hz
 - Power consumption: approx. 49 W
 - Luminous flux: 7000 lm
 - Luminous efficiency: 143 lm/W
 - Direct light portion: approx. 34%
 - Color of light: neutral white, approx. 4000 K
 - Color rendering index: Ra > 80
 - Color tolerance: < 3 SDCM
 - Luminance: <2500 cd/m²
 - UGR class: < 16
- **Supply Schedule**
 - 1 Knürr LED pendant with radio-controlled unit and push-button unit
 - 1 Mounting material



Knürr® Console LED pendant ACC20019

Picture: Herbert Waldmann GmbH & Co. KG

Model	Order no.	UP
Knürr® LED pendant	00.350.703.9	1 unit



ACC20013

SERVICE & MAINTENANCE

ESSENTIAL



SCOPE OF SERVICES:

- **24/7 service hotline** – available at all times for rapid support from our experts
- **Reliable fault rectification** – service call-out within a maximum of 10 working days
- **Replacement parts included** – no additional material costs in the event of a fault

Knürr® Service – ESSENTIAL

Description	Order-nr.
ESSENTIAL Service 24 months (2Y)	94.000.024.0
ESSENTIAL Service 36 months (3Y)	94.000.036.0
ESSENTIAL Service 48 months (4Y)	94.000.048.0
ESSENTIAL Service 60 months (5Y)	94.000.060.0

Knürr® proactive on-site maintenance

Description	Order-nr.
Maintenance	94.001.000.0
Maintenance with DGUV/V3	94.001.000.0000001
Maintenance with Thermoscan	94.001.000.0000002

PREMIUM



SCOPE OF SERVICES:

- **24/7 service hotline** – available at all times for rapid support from our experts
- **Reliable fault rectification** – service call-out within a maximum of 5 working days
- **Replacement parts included** – no additional material costs in the event of a fault
- **On-site repairs included** – travel costs and labour costs are already included in the service package

Knürr® Service – PREMIUM

Description	Order-nr.
PREMIUM Service 24 months (2Y)	94.000.024.1
PREMIUM Service 36 months (3Y)	94.000.036.1
PREMIUM Service 48 months (4Y)	94.000.048.1
PREMIUM Service 60 months (5Y)	94.000.060.1
PREMIUM Service 72 months (6Y)	94.000.072.1
PREMIUM Service 84 months (7Y)	94.000.084.1
PREMIUM Service 96 months (8Y)	94.000.096.1
PREMIUM Service 108 months (9Y)	94.000.108.1
PREMIUM Service 120 months (10Y)	94.000.120.1

*In accordance with Knürr service terms and conditions

Ergonomically designed products and solutions from a single source

Knürr GmbH is one of the world's leading specialists for innovative solutions in safety- and performance-critical control centres and command rooms. For more than 50 years, the company, headquartered in Germany, has been delivering tailor-made and fully integrated workspace systems designed for demanding 24/7 operations.

Learn more about Knürr solutions and services at
www.knuerr.com

Knürr GmbH
 Mariakirchener Straße 38
 94424 Arnstorf
 Germany
 T +49 8723 28 0
 F +49 8723 28 138
info@knuerr.com
www.knuerr.com



knürr
World of control rooms